


BURNERS WIRED WITH 4-COND. CORD ASSY
 TO LOWER BURNER
 BLACK 12 GA
 TO UPPER BURNER
 BLACK 12 GA

ALL SWITCH GROUNDS ARE JUMPED TOGETHER AND GROUNDED TO BOX AND GROUNDING SCREW.

NOTE:
 MUST WIRE ALL 70 AMP RELAYS PER POST NUMBERS POST 86 IS (+) PLUS POLARITY

10 CONDUCTOR WIRE FROM CAB TO REAR BOX TO SWITCH, BARRIER STRIP AND GROUND AS SHOWN

REV. CHANGED 30 AMP BREAKERS TO 40 AMP AND 50 AMP TO 20 AMP
 FHK/RICK 9-29-08

| | | | |
|--------------------------|---------------|--|--------------|
| QTY | NEXT ASS'Y | MADE BY | BEARCAT |
| ? | -----???????? | APPROVED | |
| | | MATERIAL | |
| | | SEE PRINTED B.O.M. | |
| | | DRAWING NO. | |
| | | FINISH | |
| TITLE | |  BEARCAT MFG. 3650 SABIN BROWN RD. WICKENBURG, AZ 85390 (928) 884-7851 | |
| SCH REAR CNTRL BX SERIAL | | SYS 2003-2009 W/CAB CTRL | |
| PART NO. | | SCH-24662 | |
| STANDARD | .X | .XX | .XXXXXXX |
| TOLERANCE | +0.02 | +0.10 | +0.003 |
| | | | ANG. X/X |
| | | | SCALE |
| | | | NDNE |
| | | | SHEET 1 OF 1 |